

# CamtectAU660 HiCover White

## RecoatableAcrylicUrethane



### FEATURES

**Camtect AU660 HiCover White** is a premium quality two component non-yellowing acrylic modified polyurethane.

Especially formulated for the harsh West Australian climate, **Camtect AU660 HiCover White** will provide a high gloss finish with excellent gloss retention, chemical resistance and outstanding durability.

Due to its acrylic modification, **Camtect AU660 HiCover White** is easily recoated, even after years of exterior exposure.

### RECOMMENDED USES

**Camtect AU660 HiCover White** is the perfect choice when a high gloss, long lasting chemical resistant coating is desired for cosmetic effect. It finds uses in all the following areas:

- Marine industry
- Chemical Industry
- Road and rail tankers
- General construction

### SPECIFICATION DATA

<b>Colour:</b>	High Opacity White	<b>Mixed Volume Solids:</b>	~46% <sup>(1)</sup>
<b>Finish:</b>	High Gloss	<b>Dry Film Thickness:</b>	40 - 50µ DFT
<b>Mixed Density:</b>	~1.25 g/cc <sup>(1)</sup>	<b>Wet Film Thickness:</b>	95 - 120µ WFT <sup>(1)</sup>
<b>Packaging:</b>	4,10 and 20 litre kits	<b>Coverage:</b>	~ 10 m <sup>2</sup> / litre @ 40µ DFT
<b>Mix Ratio:</b>	4 parts base: 1 part hardener	<b>Number of Coats:</b>	2 coats optimum
<b>Application:</b>	Spray, small areas by brush.	<b>Pot Life:</b>	8 hours @ 24°C
<b>Cleanup:</b>	Thinner AU160	<b>Touch Dry:</b>	30 minutes @ 24°C
<b>Storage:</b>	Store under cool dry conditions away from heat and sources of ignition.	<b>Dry to Recoat:</b>	16 hours minimum
		<b>Hard Dry:</b>	16 hours
		<b>Full Cure:</b>	7 days

(1) Based on Camtect AU660 HiCover White Kit

### PERFORMANCE

<b>Temperature Resistance:</b>	Up to 120°C dry heat
<b>Abrasion Resistance:</b>	Excellent
<b>Weatherability:</b>	Excellent
<b>Solvent Resistance:</b>	Excellent
<b>Chemical Resistance:</b>	Very Good.

## DIRECTIONS FOR USE

Mix 4 parts by volume of **Camtect AU660 HiCover White Part A** with 1 part by volume of **Camtect AU660 Part B**. Allow to stand for 10 minutes prior to application.

If applying by conventional spray then thinning 5-10% with **Cameleon Thinner AU160** may be added as necessary.

**Camtect AU660 HiCover White** is best applied by conventional or airless spray. Ensure that the air-lines are free from any moisture otherwise film defects may occur. If applying by roller, use a 2 pack or foam roller and thin 15-20% with AU161 Thinner.

Provide adequate natural ventilation during use. Wash equipment immediately after use with **Cameleon Thinner AU160**.

**DO NOT apply if temperature is below 10°C or if relative humidity is >85%.**

### Typical Specifications

Surface	*Preparation	System	Dry Film Build
Steel (Corrosive environment)	For best performance abrasive blast to AS1627.4 Class 2 ½ ; if this is impractical then prepare surface to AS1627.7	1. Campoxy LP546	50µ
Steel		2. Campoxy EHB585	200µ
		3. Camtect AU660 HICOVER WHITE	40 - 50µ
		4. Camtect AU660 HICOVER WHITE <sup>(2)</sup>	40 - 50µ
		1. Campoxy LP546	50µ
		2. Camtect AU660 HICOVER WHITE	40 - 50µ
		3. Camtect AU660 HICOVER WHITE <sup>(2)</sup>	40 - 50µ
Stainless steel, aluminium. Zinc alum or galvanised surfaces	Thoroughly scrub the surface to remove any white corrosion products and surface contamination (oil, grease etc). Prepare substrate to SSPC-SP-1.	1. Cametch VP628	15 - 20µ
		2. Campoxy LP546	50µ
		3. Camtect AU660 HICOVER WHITE	40 - 50µ
		4. Camtect AU660 HICOVER WHITE <sup>(2)</sup>	40 - 50µ

*(2) Second coat of Camtect AU660 HICOVER WHITE optional but recommended.*

## PRECAUTIONS

*\*Note: The figures quoted for pot-life and drying times may vary with local conditions - such as ambient temperature and humidity, storage conditions, and volume mixed. If the temperature is high (>25°C), the material is stored in the open, or a large volume is mixed, then the pot-life will be significantly reduced.*

**IMPORTANT!** See the Safety Data Sheet (SDS) for health and safety information prior to use.

## CAMELEON COATINGS

### Manufacturers of a complete range of quality paints

A Division of Red Fire Holdings PTY Ltd ABN 65 009 407 381  
 26 Paramount Drive, Wangara, Western Australia 6065  
 PO Box 1473, Wangara, Western Australia 6947  
 Telephone (+61) 8 9302 2577 Fax (+61) 8 9302 2578  
[email@cameleon.com.au](mailto:email@cameleon.com.au)  
[www.cameleon.com.au](http://www.cameleon.com.au)

#### Disclaimer

This is not a specification, and all the information is given in good faith. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated, use and whether there is any infringement of patents is the sole responsibility of the user. The manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury. For application in special conditions, consult the manufacturer for detailed recommendations.