

Rooftop

100%AcrylicExteriorCoating



FEATURES

Rooftop is a premium quality water borne 100% acrylic coating designed specifically to stand up to the harsh UV rays experienced throughout Australia.

Rooftop dries to a tough, flexible film which is impervious to water and affords excellent protection from the extremes of Australian weather.

RECOMMENDED USES

Rooftop is the perfect choice for exterior roof coating. It can be applied to suitably prepared:

- Cement and concrete roof tiles
- Timber
- Galvanised iron
- Cementitious and brick surfaces
- Fibre board
- Aged colorbond roofing

SPECIFICATION DATA

Generic Type:	Water borne Acrylic.	Volume Solids:	~31% ⁽¹⁾
Finish:	Satin	Dry Film Thickness:	40 – 50 µ.
Colour:	White, Clear <i>(Standard Cameleon Colour Range)</i>	Wet Film Thickness:	130 - 160 µ.
Density:	~1.20 g/cc ⁽¹⁾	Coverage:	6 - 8 m ² / litre ⁽¹⁾
Packaging:	4,10 and 20 litre.	Number of coats:	2 coats
Application:	Brush, Roller and spray	Touch Dry:	30 minutes
Thinner:	Water	Dry to Recoat:	2 hours
Cleanup:	Water.	Hard Dry:	8 hours.
		Storage:	Store under cool dry conditions.

⁽¹⁾ For White, may vary depending on colour.

DIRECTIONS FOR USE

Ensure all surfaces are clean, dry, and free from oil, grease and dust. Cement or clay tiles should be cleaned with high pressure water and allowed to dry prior to coating. Metal surfaces should be degreased and rust free.

Rooftop is easily applied by brush, roller or airless spray. Apply unthinned, however, a maximum of 10% water may be added for the first coat over absorbent surfaces. A finishing coat of **Rooftop Clear** can be applied to increase the system life.

Stir well and ensure colour (if tinted) is as required before use. Provide adequate natural ventilation during use. Wash equipment immediately after use with water.

DO NOT apply if temperature is below 10°C, or relative humidity is above 85%.

Typical Specifications

Surface	Preparation	System	Dry Film Build
Previously painted surfaces	Remove all loose or peeling paint. Repair the surface, thoroughly clean and allow to dry.	1. <i>Rooftop All Purpose Clear.</i>	40 - 50µ
Aged Cement or clay tiles	High pressure water wash to remove any surface contamination. Allow to dry.	2. Rooftop (colour) 3. Rooftop (colour) 4. Rooftop Clear ⁽²⁾	40 - 50µ 40 - 50µ 40 - 50µ
New cement or clay tiles, cement render and fibre board	Thoroughly clean the surface to remove any loose material. Ensure that the surface is clean, dry and dust free.	1. <i>Rooftop All Purpose Clear</i> 2. Rooftop (colour) 3. Rooftop (colour) 4. Rooftop Clear ⁽²⁾	40 - 50µ 40 - 50µ 40 - 50µ 40 - 50µ
Steel or galvanised surfaces	Thoroughly scrub the surface to remove any white corrosion products and surface contamination (oil, grease etc). Prepare substrate to SSPC-SP-1.	1. Galvaprime WB137 2. Rooftop (colour) 3. Rooftop (colour) 4. Rooftop Clear ⁽²⁾	25 - 30µ 40 - 50µ 40 - 50µ 40 - 50µ

⁽²⁾ *Rooftop Clear may be applied if additional protection is desired.*

PRECAUTIONS

See the Safety Data Sheet (SDS) for health and safety information prior to use.

CAMELEON COATINGS

Manufacturers of a complete range of quality paints

A Division of Red Fire Holdings PTY Ltd ABN 65 009 407 381
26 Paramount Drive, Wangara, Western Australia 6065
PO Box 1473, Wangara, Western Australia 6947
Telephone (+61) 8 9302 2577 Fax (+61) 8 9302 2578
email@cameleon.com.au
www.cameleon.com.au

Disclaimer

This is not a specification, and all the information is given in good faith. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated, the manner of use and whether there is any infringement of patents is the sole responsibility of the user. The manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury. For application in special conditions, consult the manufacturer for detailed recommendations.